





板式链/提升链


LEAF CHAINS & HOISTING CHAINS



板式链 Leaf chains





链板组合
Plate bcing



ISO 链号 ISO Chain No.	ANSI 链号 ANSI Chain No.	节距 Pitch P	链板组合 Plate bcing	链板高度 Plate depth h ₂	链板厚度 Plate thickness T	销轴直径 Pin diameter d ₂	销轴长度 Pin length L	抗拉强度 Tensile strength Q _{min}	平均抗拉强度 Average tensile strength Q ₀	每米长重 Weight per meter q
		P mm		h ₂ mm	T mm	d ₂ mm	L mm	Q _{min} kN/bf	Q ₀ kN	q kg/m
LH0822	BL422	12.700	2 × 2	12.07	2.03	5.09	11.05	22.2/5045	27.6	0.60
LH0823	BL423		2 × 3				13.16	22.2/5045	27.6	0.75
LH0834	BL434		3 × 4				17.40	33.4/7591	41.4	1.05
LH0844	BL444		4 × 4				19.51	44.5/10114	56.0	1.20
LH0846	BL446		4 × 6				23.75	44.5/10114	56.0	1.46
LH0866	BL466		6 × 6				27.99	66.7/15159	81.7	1.77
LH0888	BL488		8 × 8				36.45	89.0/20227	109.4	2.32
LH1022	BL522	15.875	2 × 2	15.09	2.42	5.96	12.90	33.4/7591	43.1	0.90
LH1023	BL523		2 × 3				15.37	33.4/7591	43.1	1.10
LH1034	BL534		3 × 4				20.32	48.9/11114	65.6	1.50
LH1044	BL544		4 × 4				22.78	66.7/15159	84.5	1.80
LH1046	BL546		4 × 6				27.74	66.7/15159	84.5	2.20
LH1066	BL566		6 × 6				32.69	100.1/22750	125.1	2.65
LH1088	BL588		8 × 8				42.57	133.4/30318	169.5	3.50
LH1222	BL622	19.050	2 × 2	18.11	3.25	7.94	17.37	48.9/11114	68.2	1.50
LH1223	BL623		2 × 3				20.73	48.9/11114	68.2	1.80
LH1234	BL634		3 × 4				27.43	75.6/17181	102.8	2.50
LH1244	BL644		4 × 4				30.78	97.9/22250	136.9	2.90
LH1246	BL646		4 × 6				37.49	97.9/22250	136.9	3.60
LH1266	BL666		6 × 6				44.20	146.8/33364	214.2	4.30
LH1288	BL688		8 × 8				57.61	195.7/44477	217.7	5.80
LH1622	BL822	25.400	2 × 2	24.13	4.00	9.54	21.34	84.5/19204	108.2	2.40
LH1623	BL823		2 × 3				25.48	84.5/19204	108.2	3.00
LH1634	BL834		3 × 4				33.76	129.0/29318	170.0	4.20
LH1644	BL844		4 × 4				37.90	169.0/38409	214.6	4.80
LH1646	BL846		4 × 6				46.18	169.0/38409	214.6	6.00
LH1666	BL866		6 × 6				54.46	253.6/57636	324.5	7.20
LH1688	BL888		8 × 8				71.02	338.1/76841	432.7	9.60

板式链

Leaf chains

链板组合
Plate lacing


ISO 链号 ISO Chain No.	ANSI 链号 ANSI Chain No.	节距 Pitch	链板组合 Plate lacing	链板高度 Plate depth	链板厚度 Plate thickness	销轴直径 Pin diameter	销轴长度 Pin length	抗拉强度 Tensile strength	平均抗拉强度 Average tensile strength	每米长重 Weight per meter
		P		h ₂ max	T max	d ₂ max	L max	Q _{min}	Q ₀	q
		mm		mm	mm	mm	mm	kN/bf	kN	kg/m
LH 2022	BL1022	31.75	2 × 2	30.18	4.80	11.11	25.37	115.6/26272	165.8	3.57
LH 2023	BL1023		2 × 3				30.33	115.6/26272	165.8	4.45
LH 2034	BL1034		3 × 4				40.23	182.4/41454	248.7	6.19
LH 2044	BL1044		4 × 4				45.19	231.3/52568	303.6	7.04
LH 2046	BL1046		4 × 6				55.09	231.3/52568	303.6	8.77
LH 2066	BL1066		6 × 6				65.00	347.0/78863	433.7	10.50
LH 2088	BL1088		8 × 8				84.81	462.6/105136	604.1	14.00
LH 2422	BL1222	38.10	2 × 2	36.20	5.60	12.71	29.62	151.2/34363	192.0	4.96
LH 2423	BL1223		2 × 3				35.43	151.2/34363	192.0	6.16
LH 2434	BL1234		3 × 4				47.07	244.6/55591	315.9	8.55
LH 2444	BL1244		4 × 4				52.88	302.5/68750	381.1	9.76
LH 2446	BL1246		4 × 6				64.52	302.5/68750	381.1	12.16
LH 2466	BL1266		6 × 6				76.15	453.7/103113	543.6	14.61
LH 2488	BL1288		8 × 8				99.42	605.0/137500	726.0	19.36
LH 2822	BL1422	44.45	2 × 2	42.24	6.40	14.29	33.55	191.3/43477	225.7	6.89
LH 2823	BL1423		2 × 3				40.16	191.3/43477	225.7	8.55
LH 2834	BL1434		3 × 4				53.37	315.8/71772	448.3	11.61
LH 2844	BL1444		4 × 4				59.97	382.6/86954	451.2	13.24
LH 2846	BL1446		4 × 6				73.18	382.6/86954	451.2	16.51
LH 2866	BL1466		6 × 6				86.39	578.3/131431	682.4	19.79
LH 2888	BL1488		8 × 8				112.80	765.1/173886	902.8	26.35
LH 3222	BL1622	50.80	2 × 2	48.26	*7.20	17.46	39.01	289.1/65704	341.1	8.78
LH 3223	BL1623		2 × 3				46.58	289.1/65704	341.1	10.90
LH 3234	BL1634		3 × 4				61.72	440.4/100091	519.6	15.15
LH 3244	BL1644		4 × 4				69.29	573.8/131431	680.4	17.27
LH 3246	BL1646		4 × 6				84.43	578.3/131431	680.4	21.53
LH 3266	BL1666		6 × 6				99.57	857.4/194863	1000.7	25.88
LH 3288	BL1688		8 × 8				129.84	1156.5/262841	1364.6	34.29
LH 4022	BL2022	63.50	2 × 2	60.33	9.91	23.81	51.74	433.7/98568	511.7	15.95
LH 4023	BL2023		2 × 3				61.70	433.7/98568	511.7	19.78
LH 4034	BL2034		3 × 4				81.61	649.4/147590	766.2	27.46
LH 4044	BL2044		4 × 4				91.57	867.4/197163	1023.5	31.34
LH 4046	BL2046		4 × 6				111.48	867.4/197163	1023.5	39.01
LH 4066	BL2066		6 × 6				131.39	1301.1/295704	1535.2	46.63
LH 4088	BL2088		8 × 8				171.22	1734.8/394272	2046.5	62.00

*: 有两种链板厚度, 除上述表中标注的7.20mm 之外, 另一种厚度为7.52mm。客户可根据自己的需求, 自行选择。


*: We have two kinds of chain plate thickness. Besides the 7.20mm in above table, the other thickness is 7.52mm. Customers can choose according to needs.

板式链

Leaf chains




链板组合
Plate bcing




D N /ISO 链号 D N /ISO Chain No.	节距 Pitch	链板组合 Plate bcing	链板高度 Plate depth	链板厚度 Plate thickness	销轴直径 Pin diameter	销轴长度 Pin length	抗拉强度 Tensile strength	平均抗拉强度 Average tensile strength	每米重量 Weight per meter
	P		h2 max	T max	d2 max	L max	Q min	Q ₀	q
	mm		mm	mm	mm	mm	kN /bf	kN	kg/m
LL0622	9.525	2 × 2	8.2	1.04	3.28	6.2	9.0/2023	9.9	0.22
LL0644		4 × 4				10.7	18.0/4046	19.8	0.42
LL0666		6 × 6				14.9	24.9/5598	27.4	0.62
LL0822	12.700	2 × 2	10.6	1.60	4.45	8.9	18.2/4094	20.4	0.42
LL0844		4 × 4				15.6	36.4/8188	40.7	0.84
LL0866		6 × 6				22.0	54.6/12283	60.0	1.24
LL0888		8 × 8				28.5	72.8/16378	80.0	1.64
LL1022	15.875	2 × 2	13.7	1.60	5.08	9.2	22.7/5107	25.5	0.54
LL1044		4 × 4				15.8	45.4/10213	51.0	1.06
LL1066		6 × 6				22.1	68.1/15321	76.3	1.57
LL1088		8 × 8				28.8	90.8/20427	101.9	2.10
LL1222	19.050	2 × 2	16.0	1.85	5.72	10.4	29.5/6637	33.2	0.73
LL1244		4 × 4				17.9	59.0/13273	66.4	1.44
LL1266		6 × 6				25.4	88.5/19910	99.7	2.15
LL1288		8 × 8				32.9	118.0/26547	132.9	2.84

板式链

Leaf chains




链板组合
Plate lacing



DIN/ISO 链号 Chain No.	节距 Pitch	链板组合 Plate lacing	链板高度 Plate depth	链板厚度 Plate thickness	销轴直径 Pin diameter	销轴长度 Pin length	抗拉强度 Tensile strength	平均抗拉强度 Average tensile strength	每米重量 Weight per meter
	P		h ₂ max	T max	d ₂ max	L max	Q _{min}	Q ₀	q
	mm		mm	mm	mm	mm	kN/bf	kN	kg/m
LL1622	25.40	2×2	21.00	3.10	8.28	17.2	58.0/13182	76.3	1.52
LL1644		4×4				29.6	116.0/26363	152.6	2.90
LL1666		6×6				42.4	174.0/39545	228.9	4.30
LL1688		8×8				54.9	232.0/52726	305.2	5.71
LL2022	31.75	2×2	26.40	3.70	10.19	20.1	95.0/21591	109.2	2.33
LL2044		4×4				33.8	190.0/43182	218.5	4.40
LL2066		6×6				50.1	285.0/64773	324.6	6.79
LL2088		8×8				64.0	380.0/86363	435.1	8.90
LL2422	38.10	2×2	33.40	5.00	14.63	28.4	170.0/38363	195.5	4.47
LL2444		4×4				46.3	340.0/77273	380.8	8.22
LL2466		6×6				66.4	510.0/115909	571.2	12.22
LL2488		8×8				86.6	680.0/154545	775.2	16.30
LL2822	44.45	2×2	37.08	6.00	15.90	32.2	200.0/45455	245.0	5.40
LL2844		4×4				56.4	400.0/90909	490.0	10.53
LL2866		6×6				80.8	600.0/136363	735.0	15.68
LL2888		8×8				105.2	800.0/181818	980.0	20.83
LL3222	50.80	2×2	42.00	6.40	17.81	34.8	260.0/59091	291.2	6.39
LL3244		4×4				60.6	520.0/118182	582.4	12.46
LL3266		6×6				86.4	780.0/177272	873.6	18.52
LL3288		8×8				112.2	1040.0/233970	1176.0	24.65
LL4022	63.50	2×2	52.76	8.00	22.89	42.2	360.0/81818	403.2	10.36
LL4044		4×4				74.4	780.0/177273	873.6	20.22
LL4066		6×6				106.5	1080.0/245454	1209.6	30.07
LL4088		8×8				140.0	1440.0/323959	1747.2	39.98
LL4822	76.20	2×2	63.88	10.00	29.24	54.6	560.0/127272	627.2	15.94
LL4844		4×4				92.6	1120.0/254545	1554.4	31.38
LL4866		6×6				133.4	1680.0/377953	1880.0	46.94
LL4888		8×8				174.2	2240.0/509091	2508.8	62.36


板式链

Leaf chains



JIS 链号 JIS Chain No.	节距 Pitch	链板组合 Plate config	链板高度 Plate depth	链板厚度 Plate thickness	销轴直径 Pin diameter	销轴长度 Pin length	抗拉强度 Tensile strength	平均抗拉强度 Average tensile strength	每米长重 Weight per meter
	P		h _{2 max}	T _{max}	d _{2 max}	L _{max}	Q _{min}	Q ₀	q
	mm		mm	mm	mm	mm	kN/lbf	kN	kg/m
AL322	9.525	2×2	7.7	1.30	3.58	6.80	9.0/2045	10.2	0.23
AL344		4×4				11.60	18.0/4090	20.0	0.46
AL422	12.700	2×2	10.4	1.50	3.96	8.30	14.7/3304	16.9	0.39
AL444		4×4				14.40	29.4/6609	35.2	0.74
AL466		6×6				20.50	44.0/9891	52.7	1.13
AL522	15.875	2×2	12.8	2.03	5.08	11.05	24.5/5508	28.6	0.64
AL534		3×4				17.00	36.8/8273	46.0	1.10
AL544		4×4				19.40	48.9/10993	62.4	1.25
AL566		6×6				27.50	73.4/16500	93.8	1.79
AL622	19.050	2×2	15.6	2.42	5.94	13.00	33.4/7508	44.4	0.87
AL644		4×4				22.70	66.7/14994	78.8	1.70
AL666		6×6				32.20	100.1/22502	118.6	2.53
AL688		8×8				42.20	133.4/29988	156.6	3.37
AL822	25.400	2×2	20.8	3.25	7.92	16.20	57.9/13016	68.6	1.57
AL844		4×4				29.40	115.7/26009	135.6	3.08
AL866		6×6				44.20	173.5/39003	202.3	4.62
AL888		8×8				55.50	231.4/52019	245.0	6.12
AL1022	31.750	2×2	25.6	4.00	9.53	19.60	84.5/18996	107.1	2.51
AL1044		4×4				36.40	169.0/37991	203.6	4.95
AL1066		6×6				52.30	253.5/56987	315.3	7.39
AL1088		8×8				68.50	338.0/75982	421.2	9.83
AL1222	38.100	2×2	30.5	4.80	11.10	24.30	120.1/26998	151.1	3.65
AL1244		4×4				43.80	240.2/53997	299.7	7.05
AL1266		6×6				63.20	360.3/80995	426.3	10.50
AL1288		8×8				82.60	480.4/107994	568.4	14.03
AL1444	44.450	4×4	36.4	5.60	12.70	51.30	302.5/68002	413.6	9.80
AL1466		6×6				74.50	453.7/101992	620.4	14.66
AL1644	50.800	4×4	41.6	6.40	14.21	58.00	382.5/85986	522.8	12.90
AL1666		6×6				83.80	573.8/128990	783.6	19.27
AL1688		8×8				109.50	765.0/171972	1045.5	25.64

板式链 Leaf chains




东华链号 Donghua Chain No.	节距 Pitch	链板组合 Plate bcng	链板高度 Plate depth	链板厚度 Plate thickness	销轴直径 Pin diameter	销轴长度 Pin length	抗拉强度 Tensile strength	平均抗拉强度 Average tensile strength	每米长重 Weight per meter
	P		h ₂ max	t/T max	d ₂ max	L max	Q _{min}	Q ₀	q
	mm		mm	mm	mm	mm	kN/bf	kN	kg/m
FL644	5.940	4×4	4.7	0.60	1.85	6.2	6.50/1477	7.8	0.13
FL666		6×6				9.3	9.75/2216	11.8	0.20
FL688		8×8				12.0	13.00/2955	15.6	0.25
FL523	8.000	3×2	6.3	1.00	2.31	6.7	7.00/1575	7.4	0.18
*FL523F1	8.000	3×2	6.3	1.30/1.00	2.31	6.3	7.00/1575	7.4	0.25
*FL523F3	8.000	3×2	7.6	1.30/1.04	3.10	8.0	7.00/1575	8.0	0.33
*FL523F4	8.000	3×2	7.6	1.30/1.04	2.31	7.6	7.00/1576	8.0	0.32
FL844	8.000	4×4	6.9	0.73	2.31	7.9	10.00/2273	12.1	0.25
*FL823F1	8.000	3×2	7.6	1.30/1.04	3.15	7.8	11.00/2472	11.8	0.32
FL922	9.525	2×2	8.7	1.04	3.28	6.2	10.00/2273	12.1	0.22
FL944		4×4				10.4	21.00/4724	24.7	0.43
FL945		4×5				11.5	21.00/4724	23.0	0.50
FL956		6×5				14.0	25.50/5732	28.0	0.60
FL966		6×6				14.9	31.00/7045	36.8	0.65
FL988		8×8				19.0	42.00/9450	46.2	0.87
FL966F3	9.525	6×6	8.7	1.15	3.28	16.2	33.10/7441	36.5	0.75
FL922F4	9.525	2×2	8.5	1.60	3.90	8.6	12.50/2810	13.8	0.37
LF10	10.000	3×3	7.5	1.20	3.20	10.6	14.00/3150	15.5	0.39
LF1234	12.000	4×3	10.0	2.03	3.96	17.6	15.45/3476	17.0	0.85
LF1246	12.000	△6×4	10.8	1.60	5.08	18.7	30.00/6748	33.0	1.05
F1266F1	12.700	△6×6	9.0	1.60	3.70	21.6	45.00/10123	50.0	0.92
F122	12.700	2×2	8.2	1.00	3.58	7.0	11.43/2598	13.6	0.19
F1223	12.700	3×2	10.2	2.03	4.45	12.8	20.00/4545	23.8	0.61
FL1244	12.700	4×4	10.2	1.70	4.45	16.7	44.00/10000	52.3	0.83
F1023	15.875	3×2	14.3	2.42	4.75	15.9	25.00/5625	27.5	1.11
FLC 534	15.875	3×4	12.7	1.85	5.08	15.3	40.40/9181	44.4	0.99
FLC 545		5×4				19.2	54.30/12340	59.7	1.27
FLC 556		6×5				22.7	67.60/15363	74.3	1.54
FLC 567		7×6				26.8	80.80/18176	89.0	1.82


注：带*表示链板为直边形；带△表示链板组合特殊

Note: * means straight link plate; △ means special link plate combination

板式链 Leaf chains



链板组合
Plate bcing




东华链号 Donghua Chain No.	节距 P itch	链板组合 P late bcing	链板高度 P late depth	链板厚度 P late thickness	销轴直径 P in diam eter	销轴长度 P in length	抗拉强度 Tens ile strength	平均抗拉强度 Average tens ile strength	每米长重 W eight per m eter
	P		h2 m ax	t/T m ax	d2 m ax	L m ax	Q _{m in}	Q ₀	q
	m m		m m	m m	m m	m m	kN /bf	kN	kg/m
FLC 578	15.875	8×7	12.70	1.85	5.08	30.8	90.0/20250	99.0	2.10
CTL566	15.875	6×6	15.10	2.10	5.08	28.0	78.0/17534	86.0	2.44
CTBLL588	15.875	8×8	14.80	1.70	5.94	30.7	85.0/19108	105.0	2.59
*CH25	17.000	2×1	9.00	1.60	4.00	7.5	6.0/1348	7.5	0.27
LF1866	18.550	6×6	15.80	3.00	6.00	39.8	106.0/23845	116.6	3.58
LF1966	19.050								3.53
F19S-44	19.050	4×4	14.70	2.25	5.98	21.8	76.5/17210	84.5	1.55
F19S-66		6×6				31.0	115.0/25870	126.5	2.31
F19V-44	19.050	4×4	15.20	2.42	6.50	22.4	71.0/16136	84.3	1.73
F19V-66		6×6				32.3	106.0/24090	125.9	2.57
F19VF1-66	19.050	6×6	17.60	2.42	6.50	32.3	164.0/36867	180.4	3.22
F19V-88	19.050	8×8	15.20	2.42	6.50	42.4	142.0/31922	156.2	3.41
FLC 623	19.050	3×2	14.50	1.85	5.72	12.5	30.0/6744	33.0	0.81
FLC 634	19.050	4×3	14.50	1.85	5.72	16.1	46.0/10341	50.6	1.12
FL2044	20.000	4×4	16.00	2.42	5.30	22.4	67.0/15062	73.7	1.83
FLC 823	25.400	3×2	19.46	3.25	8.28	20.9	65.0/14612	72.0	1.86
FLC 834		4×3				27.4	100.0/22500	110.0	2.57
FLC 845		5×4				34.2	130.0/29224	143.0	3.30
FLC 856		6×5				40.5	166.0/37343	183.0	4.00
FLC 867		7×6				47.0	195.7/44024	215.3	4.70
FLC 878		8×7				53.6	227.5/51180	250.5	5.40
F25-34	25.400	3×4	23.40	3.05/4.00	10.85	28.6	125.0/28120	137.5	3.64
F25-66		6×6				44.1	250.0/56240	275.0	5.93
F25-66F1	25.000	6×6	24.00	3.00	10.85	42.0	147.0/33046	190.0	5.65
FLC 1034	31.750	4×3	25.40	3.25	9.53	28.4	82.7/18591	91.0	3.52
FLC 1045		5×4				34.3	110.0/24745	121.0	4.49
FLC 1056		6×5				40.6	137.9/31340	151.0	5.44
FLC 1067		7×8				47.2	165.4/37590	181.9	6.42
FLC 1078		8×7				53.8	193.0/43863	212.0	7.40
LF31109	31.750	10×9	27.00	4.00	12.00	83.0	440.0/98915	500.0	12.70
P35-44	35.000	△4×4	30.00	4.00	12.00	37.7	100.0/22500	110.0	5.96
LF8844F1	88.900	4×4	84.00	13.50	40.00	122.0	1950.0/438360	2145.0	60.60
D90F1	90.000	8×8	70.00	6.30	36.00	113.0	980.0/220460	1078.0	41.20
LF105	105.000	11×10	80.00	6.00	40.00	143.0	1470.0/330690	1690.5	64.38

注：带*表示链板为直边形；带△表示链板组合特殊

Note: * means straight link plate; △ means special link plate combination

板式链

Leaf chains




东华链号 Donghua Chain No.	节距 Pitch	链板组合 Plate lacing	链板高度 Plate depth	链板厚度 Plate thickness	销轴直径 Pin diameter	销轴长度 Pin length	抗拉强度 Tensile strength	平均抗拉强度 Average tensile strength	每米长重 Weight per meter
	P		h ₂ max	t/T max	d ₂ max	L max	Q _{min}	Q ₀	q
	mm		mm	mm	mm	mm	kN/bf	kN	kg/m
AL0522	8.000	2×2	7.10	0.80	2.31	5.00	4.4/990	4.6	0.15
AL0544		4×4				8.20	8.8/1980	9.3	0.28
AL0566		6×6				11.60	13.0/2922	13.7	0.42
AL322F1	9.525	2×2	7.00	1.30	3.58	7.50	9.3/2092	9.8	0.22
AL344F1		4×4				12.80	18.5/4162	19.4	0.42
AL366F1		6×6				18.20	27.8/6254	29.2	0.62
AL388F1		8×8				23.60	37.0/8323	38.8	0.82
AL322HF2	9.525	2×2	7.70	1.50	3.58	7.60	10.0/2248	10.5	0.24
*AL344F3	9.525	4×4	7.70	1.20	3.58	11.60	18.0/4046	18.9	0.49
AL344F4	9.525	4×4	7.90	1.57	3.58	15.00	25.0/5620	26.3	0.63
AL866F1	25.400	6×6	20.50	3.00	7.92	40.30	135.0/30370	148.5	4.40
AL822F3	25.400	2×2	20.80	3.25	7.92	15.90	57.9/13016	70.0	1.61
AL10910F1	31.750	10×9	27.00	4.00	12.00	83.00	400.0/89923	441.0	11.80
AL1066F2	31.750	6×6	25.60	4.00	9.53	52.20	265.0/59574	305.0	7.43
AL1044F1	31.750	4×4	22.80	4.15	10.19	37.90	214.0/48107	234.5	4.32
AL1266F1	38.100	6×6	30.00	4.80	13.30	64.30	420.0/94482	462.0	9.68
BL432F1	12.700	△3×2	11.60	2.03	4.45	12.60	22.0/4946	24.0	0.76
LH0844F5	12.700	4×4	12.07	1.60	5.08	16.00	27.5/6182	30.0	1.01
LH0832F6	12.700	△3×2	12.07	2.03	4.45	13.16	19.8/4451	23.0	0.77
LH081010F8	12.700	10×10	12.07	2.03	5.94	44.80	120.0/26977	130.0	6.35
LH0844F	12.700	4×4	12.07	1.60	5.08	15.70	44.48/10000	48.9	1.01
BL544F1	15.875	4×4	14.60	2.37	5.94	22.50	80.0/17985	85.0	1.76
LH1034F2	15.875	3×4	15.00	2.42	5.94	20.30	65.0/14612	70.0	1.64
BL544F8	15.875	4×4	15.00	1.70	5.80	17.00	46.0/10341	53.0	1.33
LH1223F1	19.050	2×3	15.60	2.42	5.94	20.30	29.4/6610	32.5	1.50
LH1245F1		4×5				25.20	39.2/8812	43.0	1.91
LH1223F3	19.050	2×3	18.10	3.25	7.93	19.90	68.65/15433	71.0	1.95
LH1234F3		3×4				26.60	102.97/23148	108.8	2.69


注：带*表示链板为直边形；带△表示链板组合特殊
Note: * means straight link plate; △ means special link plate combination

板式链

Leaf chains




链板组合
Plate bcing




东华链号 Donghua Chain No.	节距 Pitch	链板组合 Plate bcing	链板高度 Plate depth	链板厚度 Plate thickness	销轴直径 Pin diameter	销轴长度 Pin length	抗拉强度 Tensile strength	平均抗拉强度 Average tensile strength	每米长重 Weight per meter
	P		h ₂ max	t/T max	d ₂ max	L max	Q _{min} kN/bf	Q ₀ kN	q kg/m
BL666F1	19.050	6 x 6	18.10	2.35	6.50	31.70	130.0/29224	143.0	3.30
*BL666G L	19.050	6 x 6	16.00	3.00	6.25	40.00	100.0/22480	110.0	3.80
BL866F1	25.400	6 x 6	24.10	3.10/4.00	10.85	45.70	200.0/44992	220.0	6.14
BL834F2		3 x 4				29.50	120.0/26995	132.0	3.76
BL834F3	25.400	3 x 4	24.10	4.00	10.90	32.90	142.0/31944	156.2	4.44
BL866F3		6 x 6				52.20	253.6/57050	279.0	7.48
BL834F5	25.400	3 x 4	24.10	3.10/4.00	10.90	28.00	120.0/26995	132.0	3.64
BL866F5	25.400	6 x 6	24.10	3.30/4.00	10.90	45.30	200.0/44992	220.0	4.94
LH1646F3	25.400	4 x 6	24.10	4.00	9.53	44.20	233.0/52378	256.5	6.22
BL844F8	25.400	4 x 4	25.10	3.00	10.90	30.00	120.0/26976	135.0	3.84
LH2066F1	31.750	6 x 6	29.70	4.09	11.10	55.70	303.0/68177	365.0	9.42
BL1046F2	31.750	4 x 6	29.70	4.00	11.10	47.00	231.3/51996	266.0	7.74
LH2054F4	31.750	△5 x 4	29.70	5.60	11.10	56.50	280.0/62947	340.0	9.56
LH281010F1	44.450	10x10	36.10	5.00	14.27	108.00	1220.0/274256	1400.0	22.20
LH3288F1	50.800	8x8	47.80	6.90	20.20	122.00	1200.0/269950	1320.0	33.53
LH3266F2	50.800	6x6	48.20	7.00	17.46	91.80	867.0/195040	953.7	24.52
LH3244F6	50.800	4 x 4	42.00	6.00	17.46	56.00	430.0/96667	505.0	11.96
LH3288F9	50.800	8x8	48.20	6.40	17.46	112.00	1040.0/233792	1144.0	31.89
LH3288F10	50.800	8 x 8	48.20	9.50	19.84	164.20	2100.0/472080	2310.0	51.63
LL0622F4	9.525	2 x 2	8.40	1.04	3.28	6.20	10.0/2248	10.5	0.23
LL0634F4		3 x 4				9.70	15.5/3484	16.5	0.39
LL0644F4		4 x 4				10.70	21.0/4720	22.0	0.44
LL0666F4		6 x 6				14.90	31.0/6970	33.0	0.65

注：带*表示链板为直边形；带△表示链板组合特殊
Note: * means straight link plate; △ means special link plate combination

板式链 Leaf chains



链板组合
Plateacing




东华链号 Donghua Chain No.	节距 Pitch	链板组合 Plateacing	链板高度 Plate depth	链板厚度 Plate thickness	销轴直径 Pin diameter	销轴长度 Pin length	抗拉强度 Tensile strength	平均抗拉强度 Average tensile strength	每米长重 Weight per meter
	P		h2 max	t/T max	d2 max	L max	Qm	Qo	q
	mm		mm	mm	mm	mm	kN/bf	kN	kg/m
LL0622F7	9.525	2 x 2	8.20	1.30	3.28	7.40	10.5/2360	11.6	0.27
LL0644F7		4 x 4				12.80	21.0/4720	23.0	0.52
LL0844F6	12.700	4 x 4	11.00	1.50	4.45	14.60	37.6/8452	81.4	0.82
LL0888F1		8 x 8				27.40	77.0/17310	85.0	1.61
LL0844F7	12.700	4 x 4	11.20	1.60	4.45	15.60	36.4/8180	41.5	0.85
LL0822F13	12.700	2 x 2	10.60	1.70	4.45	9.40	22.0/4940	23.0	0.45
LL0844F13		4 x 4				16.50	40.0/8990	43.0	0.88
LL0888F2	12.700	8 x 8	11.00	1.43	4.45	25.90	77.0/17310	84.7	1.55
LL1044F7	15.875	4 x 4	13.70	1.50	5.08	15.10	48.0/10790	52.8	1.04
LL1066F3	15.875	6 x 6	13.70	1.80	5.08	24.50	86.0/19333	94.6	1.68
LL101212F4	15.875	△12x12	11.80	1.60	5.08	42.50	110.0/24728	121.0	2.47
LL101212F5	15.875	△12x12	13.70	1.50	5.08	40.50	136.2/30620	150.0	3.00
LL1266F2	19.050	6 x 6	14.50	3.00	5.72	39.50	156.8/35249	173.0	3.03
LL1266F3	19.050	6 x 6	16.00	3.00	5.72	39.50	88.5/19895	97.5	3.03
*LL1266H	19.050	6 x 6	16.13	3.00	5.72	40.00	86.7/19490	100.0	3.75
LL1266F6	19.050	6 x 6	18.50	2.90	5.72	38.75	88.2/19827	97.0	4.12
LL1622F6	25.400	2x2	20.00	3.00	8.28	15.60	58.0/13047	63.8	1.40
LL2066F6	31.750	6 x 6	30.20	4.00	13.74	56.10	310.0/69690	356.5	13.13
LL3244F2	50.800	4x4	43.10	6.00	17.76	54.00	520.0/116978	572.0	12.62
LL3244F8	50.800	4 x 4	42.00	6.00	17.81	57.00	520.0/116900	560.0	12.31
LL3288F8		8 x 8				105.50	1040.0/233800	1125.0	24.32
LL4088F2	63.500	8 x 8	52.70	8.20	22.89	140.00	1440.0/323725	1660.0	42.39
LL4888H	76.200	8x8	70.00	12.00	36.50	204.00	2630.0/591638	2893.0	83.80


注：带*表示链板为直边形；带△表示链板组合特殊
Note: * means straight link plate; △ means special link plate combination

板式链


Leaf chains



东华链号 Donghua Chain No.	节距 Pitch	链板组合 Plate lacing	链板高度 Plate depth	链板厚度 Plate thickness	销轴直径 Pin diameter	销轴长度 Pin length	抗拉强度 Tensile strength	平均抗拉强度 Average tensile strength	每米长重 Weight per meter
	P		h ₂ max	T max	d ₂ max	L max	Q _m n	Q ₀	q
	mm		mm	mm	mm	mm	kN/bf	kN	kg/m
FB156	15.875	6×6	14.7	1.70	5.08	24.0	78.0/17550	86.0	1.91
FB156S				2.03		27.5	83.5/18784	92.0	2.24
FB196	19.050	6×6	16.0	1.85	5.72	25.4	95.0/21371	105.0	1.94
FB196S				2.42		32.3	130.0/29244	143.0	3.37




链板组合
Plate lacing



东华链号 Donghua Chain No.	节距 Pitch	链板组合 Plate lacing	链板高度 Plate depth	链板厚度 Plate thickness	销轴直径 Pin diameter	销轴长度 Pin length	抗拉强度 Tensile strength	平均抗拉强度 Average tensile strength	每米长重 Weight per meter
	P		h ₂ max	T max	d ₂ max	L max	Q _m n	Q ₀	q
	mm		mm	mm	mm	mm	kN/bf	kN	kg/m
BL1266F1	38.1	6×6	35.7	5.6	12.70	78.9	453.7/102063	499.0	15.69
BL1666F4	50.8	6×6	48.2	7.2	17.46	99.2	867.0/195040	953.7	27.27
LL2488F1	38.1	8×8	33.4	5.0	14.63	94.0	680.0/152864	748.0	16.71
LL3244F1	50.8	4×4	42.0	6.0	17.81	61.6	520.0/116978	572.0	12.90
LL3266F1		6×6				86.0	780.0/175467	858.0	18.90
LL3288F1		8×8				110.0	1040.0/233956	1144.0	24.89
LL321010F1		10×10				134.3	1300.0/292445	1430.0	30.89
LL3244F3	50.8	4×4	43.1	6.0	17.76	60.0	520.0/116978	572.0	13.06
LL3266F3		6×6				84.4	780.0/175467	858.0	19.44
LL3288F3		8×8				108.6	1040.0/233956	1144.0	25.43
LL3244F4	50.8	4×4	42.0	6.4	17.81	67.5	520.0/116980	572.0	13.82
LL3266F4		6×6				92.8	780.0/175467	858.0	20.17
LL3288F7		8×8				117.0	1040.0/233800	1144.0	26.30
LL4066F1	63.5	6×6	57.5	6.3	19.85	100.0	1166.2/262162	1283.0	29.30
LL4088F1		8×8				126.0	1558.2/350283	1714.0	38.10
LL4088F3	63.5	8×8	57.5	6.0	19.85	119.0	1395.0/313596	1535.0	35.79
LL4044F4	63.5	4×4	52.7	8.0	22.89	80.8	780.0/175351	860.0	21.82
LL4888F3	76.2	8×8	73.0	7.2	34.67	138.5	1840.0/413632	2024.0	56.02
LL481010F3		10×10				165.5	2340.0/526032	2574.0	69.18


板式链 Leaf chains




东华链号 Donghua Chain No.	节距 Pitch	链板高度 Plate depth	链板厚度 Plate thickness	销轴直径 Pin diameter	销轴长度 Pin length		抗拉强度 Tensile strength	平均抗拉强度 Average tensile strength	每米长重 Weight per meter
	P	$h_{2\max}$	$T_{\max}$	$d_{2\max}$	$L_{\max}$	L_3	$Q_{\min}$	Q_0	q
	mm	mm	mm	mm	mm	mm	kN/bf	kN	kg/m
AL422F1-D 2	12.700	11.00	1.60	3.96	14.4	3.80	14.1/3172	15.5	0.50
AL522-D 2	15.875	12.80	2.03	5.10	16.0	3.90	22.0/4950	23.0	0.69
AL522-D 2F1					19.0	5.40			0.73
AL522F1-D 2	15.800	12.70	2.00	5.09	16.1	3.90	30.38/6834	32.0	0.66
AL622-DD 3F1	19.050	16.90	3.25	5.94	22.3	4.40	50.0/11240	55.0	1.44
AL644F4-D 2	19.050	14.60	3.10	5.90	22.5	4.90	36.0/8093	40.0	1.14
BL422-DD 3	12.700	12.07	2.03	5.08	31.4	11.50	22.24/50000	24.5	0.91
LH 1222-D 2	19.050	18.10	3.25	7.92	22.6	4.60	48.93/11000	54.0	1.66
LH 1222F7-DD 3					29.4	8.00	48.93/11001	55.0	1.80
LH 1222-DD 3F1					29.0	7.75	48.93/10999	53.8	1.80
LH 1246-DD 3F1					42.5	4.75	97.9/22008	112.5	3.88
LH 1622F1	25.400	24.10	4.00	9.53	34.0	8.80	84.5/19010	93.0	2.40
LH 1622-D 2					36.0	9.80			2.83
LH 1622-DD 3F1					45.0	14.30			3.04
LH 1622-DD 3F2					25.4	4.45			2.60
BL822F1-D 2	25.400	24.10	4.60	8.80	32.4	6.80	84.5/19010	93.0	3.03
BL822HF1-D 2				9.53	32.4				3.07
BL822HF2-DD 3	25.400	24.00	5.00	9.53	35.0	7.05	84.5/19010	97.5	2.55
BL1022F1-D 2	31.750	29.00	5.60	11.30	41.2	8.40	130.0/29245	143.0	4.49
BL1022H-D 2	31.750	29.70	5.60	11.10	41.2	8.40	130.0/29245	143.0	4.69
LH 2022-DD 3F1	31.750	29.70	4.80	11.10	30.4	5.50	115.6/25987	127.2	3.89
LL1222F3-D 2	19.050	14.50	2.25	5.72	22.0	6.30	44.1/9920	48.5	0.89
LL1222F5-DD 3	19.050	14.50	3.00	5.72	29.0	8.30	45.1/10139	49.5	1.17
LL1222F5-DD 3F1	19.050	14.50	3.00	5.72	22.0	4.80	45.1/10140	50.5	1.10
LL1622-D 2	25.400	21.00	3.10	8.28	36.1	11.70	58.0/13050	64.0	1.92
LL1622F7-DD 3	25.400	21.00	3.05	8.28	35.0	11.20	75.4/16950	79.2	1.85
LL1622F7-DD 3F1	25.400	20.00	3.00	8.28	30.5	9.00	58.0/13040	63.8	1.65
LL1623F1-DD 3	25.400	21.00	4.00	8.28	34.0	7.00	60.0/13488	66.0	2.70
F1422-DD 3	14.290	13.00	2.03	4.97	19.1	5.20	27.5/6182	30.0	0.76
1922V-D 2	19.050	16.70	3.17	6.10	22.6	4.65	55.0/12364	60.5	1.40
F2022-D 2	20.750	19.00	3.40	7.65	23.0	4.50	50.0/11500	55.0	1.79
F2422-D 2	23.950	22.20	3.86	8.69	27.8	5.90	60.0/13500	66.0	2.37
F2422F1-D 2	24.000	22.00	4.00	9.00	27.0	5.40	60.0/13500	66.0	2.39

板式链

Leaf chains



链板组合
Plate bcing




东华链号 Donghua Chan No.	节距 Pitch	链板组合 Plate bcing	链板高度 Plate depth	链板厚度 Plate thickness	销轴直径 Pin diameter	销轴长度 Pin length	链条长度(100节) Chain length for 100 pitches (±0.25%)	抗拉强度 Tensile strength	每米长重 Weight per meter
	P		h2 max	T max	d2 max	L max		Q min	q
	mm		mm	mm	mm	mm	mm	kN/bf	kg/m
1222	12.700	2×2	10.6	1.70	4.45	9.2	1262	21.0/4721	0.44
1234		3×4				14.2		31.0/6974	0.75
1244		4×4				16.1		42.0/9442	0.86
1256		5×6				21.1		53.0/12045	1.17
1266		6×6				23.0		63.0/14162	1.27
1288		8×8				29.9		85.0/19318	1.70
1523	15.875	2×3	12.7	1.94	5.08	12.1	1580	29.0/6590	0.75
1534		3×4				16.5		46.0/10454	1.04
1543		△4×3				16.5		46.0/10455	1.05
1544		4×4				18.6		58.0/13181	1.18
1545		4×5				20.3		58.0/13181	1.33
1556		5×6				24.0		72.0/16363	1.63
1566		6×6				26.2		87.0/19772	1.77
1567		6×7				28.0		90.0/20454	1.91
1578		7×8				32.5		101.0/22954	2.20
1588		8×8				34.0		115.0/26136	2.34
1944	19.050	4×4	15.0	2.29	5.72	21.3	1891	73.0/16590	1.58
1966		6×6				30.7		110.0/25000	2.37
1978		7×8				37.7		122.0/27426	2.98
1988		8×8				40.0		140.0/31817	3.13

注：带△表示链板组合特殊


Note: △ means special link plate combination

板式链

Leaf chains




链板组合
Plate bcing



东华链号 Donghua Chain No.	节距 Pitch	链板组合 Plate bcing	链板高度 Plate depth	链板厚度 Plate thickness	销轴直径 Pin diameter	销轴长度 Pin length	链条长度(100节) Chain length for 100 pitches (±0.25%)	抗拉强度 Tensile strength	每米长重 Weight per meter
	P		h2 max	T max	d2 max	L max		Q min	q
	mm		mm	mm	mm	mm	mm	kN/bf	kg/m
2522	25.400	2×2	20.2	3.06	8.28	15.5	2532	72.0/16186	1.47
2523		2×3				18.8		72.0/16363	1.83
2534		3×4				25.3		108.0/24545	2.55
2544		4×4				29.5		145.0/32597	2.92
2545		4×5				31.6		144.0/30727	3.26
2556		5×6				38.2		180.0/40908	3.96
2567		6×7				43.8		216.0/49090	4.68
2578		7×8				50.0		252.0/57272	5.39
2588		8×8				52.8		290.0/65908	5.77
3134	31.750	3×4	22.8	4.10	10.19	33.3	3168	160.0/35968	4.16
3144		4×4				37.5		214.0/48109	4.24
3166		6×6				54.3		304.0/68339	6.33
3188		8×8				71.1		428.0/96214	8.40
1244F3	12.700	4×4	11.0	1.43	4.45	13.9	1262	24.97/7861	0.78
1266F1		6×6				19.9		52.46/7861	1.06


空心销轴板式链 Hollow pin leaf chains




东华链号 Donghua Chain No.	节距 Pitch	链板组合 Plate bchng	链板高度 Plate depth	链板厚度 Plate thickness	销轴直径 Pin diameter		销轴长度 Pin length	抗拉强度 Tensile strength	平均抗拉强度 Average tensile strength	每米长重 Weight per meter
	P mm		h2 max mm	T max mm	d2 min mm	d3 max mm	L max mm	Q _{min} kN/bf	Q ₀ kN	q kg/m
LF36	36.513	2×2	22.3	2.03	10.2	14.4	12.0	20.0/4496	25.0	0.85
LF36F2	36.513	2×2	24.0	2.50	9.5	14.9	15.0	30.0/6744	37.5	1.19
LF36F3	36.513	2×2	24.0	2.50	10.0	14.9	15.0	30.0/6744	37.5	1.16
LF36F4	36.513	2×2	23.6	2.60	8.2	11.0	16.6	15.0/3372	30.0	1.25
LF36F6	36.513	2×2	22.0	2.60	9.5	14.5	14.5	35.0/7868	37.5	1.15
LF36F7	36.513	2×2	22.4	2.60	9.6	13.0	14.7	31.0/6969	40.5	1.05
LF36F8	36.513	2×2	23.6	2.60	10.0	13.0	16.6	15.0/3372	30.0	1.25

堆高机用板式链

Leaf chains for sky stacker




链板组合
Plate bcng




东华链号 Donghua Chain No.	节距 Pitch	链板组合 Plate bcng	链板高度 Plate depth	链板厚度 Plate thickness	销轴直径 Pin diameter	销轴长度 Pin length	抗拉强度 Tensile strength	平均抗拉强度 Average tensile strength	每米长重 Weight per meter
	P		h2 max	T max	d2 max	L max	Q _{min} kn/bf	Q ₀ kN	q kg/m
	mm		mm	mm	mm	mm			
LH 2044 (DG)	31.75	4×4	30.18	4.80	11.10	43.8	231.3/51996	254.4	7.60
LH 2066 (DG)	31.75	6×6	30.18	4.80	11.10	64.0	347.0/78008	380.0	11.65
LH 2444 (DG)	38.10	4×4	36.20	5.60	12.70	51.3	302.5/68002	332.8	10.30
LH 2466 (DG)	38.10	6×6	36.20	5.60	12.70	75.5	453.7/101992	475.0	11.52
LH 2488 (DG)	38.10	8×8	36.20	5.60	12.70	96.5	605.0/136004	665.5	21.60
LH 2844 (DG)	44.45	4×4	42.20	6.40	14.27	57.5	382.6/86008	400.0	14.12
LH 2846 (DG)	44.45	4×6	42.20	6.40	14.27	73.0	382.6/86009	400.0	17.63
LH 2866 (DG)	44.45	6×6	42.20	6.40	14.27	83.2	706.0/158709	810.0	21.09
LH 3234 (DG)	50.80	3×4	48.20	7.20	17.46	57.9	440.4/99002	506.0	15.49
LH 3244 (DG)	50.80	4×4	48.20	7.20	17.46	65.1	573.8/128990	602.0	17.67
LH 3246 (DG)	50.80	4×6	48.20	7.20	17.46	80.0	573.8/128990	602.0	22.20
LH 3266 (DG)	50.80	6×6	48.20	7.20	17.46	96.7	867.4/194991	911.0	26.70
LH 3288 (DG)	50.80	8×8	48.20	7.20	17.46	123.3	1156.5/259981	1214.0	35.00
LH 4044 (DG)	63.50	4×4	60.33	9.91	23.81	91.5	867.4/194992	954.1	31.60
LH 4066 (DG)	63.50	6×6	60.33	9.91	23.81	131.2	1301.1/292487	1496.0	48.10
LH 2466F2 (DG)	38.10	6×6	36.20	5.60	12.70	75.5	648.0/145670	710.0	11.52
LH 2488F4 (DG)	38.10	8×8	36.20	5.60	12.70	97.3	800.0/179840	880.0	21.69
LH 3266 (DGF1)	50.80	6×6	48.20	7.20	17.46	94.2	993.6/223361	1143.0	26.35
LH 3288 (DGF2)	50.80	8×8	48.20	7.20	17.46	124.5	1364.6/306774	1500.0	35.09
LH 3288F7 (DG)	50.80	8×8	48.20	7.20	17.46	127	1513.0/340122	1664.3	35.19
BL2088F2 (DG)	63.50	8×8	58.20	9.70	23.81	170.0	1734.8/389983	1995.0	56.74
LL2466 (DG)	38.10	6×6	33.40	5.00	14.63	67.4	510.0/114648	536.0	13.00
LL2866 (DG)	44.45	6×6	36.00	6.00	15.90	80.2	600.0/134880	660.0	16.31
LL4066 (DG)	63.50	6×6	52.70	8.00	22.89	106.5	1080.0/242793	1245.0	31.62
LL4088 (DG)	63.50	8×8	52.70	8.00	22.89	140.0	1400.0/314733	1650.0	42.10
LL2844 (DGF1)	44.45	4×4	36.00	6.00	15.90	54.7	400.0/89923	450.0	10.92
LL2866 (DGF1)	44.45	6×6	36.00	6.00	15.90	80.2	650.0/146120	715.0	16.20
LL3244F2 (DG)	50.80	4×4	43.10	6.00	17.76	55.0	520.0/116900	570.0	12.62
LL3244F6 (DG)	50.80	4×4	42.00	6.00	17.81	57.5	520.0/116900	570.0	12.35
LL3266F6 (DG)	50.80	6×6	42.00	6.00	17.81	81.7	780.0/175344	858.0	18.30
LL3266 (DGF1)	50.80	6×6	42.00	6.40	17.81	86.0	780.0/175344	858.0	19.53
LL3266F3 (DG)	50.80	6×6	43.10	6.00	17.76	79.9	780.0/178344	858.0	18.84
LL3288F6 (DG)	50.80	8×8	42.00	6.00	17.81	106.0	1040.0/233792	1144.0	24.30
LL3288 (DGF2)	50.80	8×8	42.00	6.40	17.81	112.0	1040.0/233792	1144.0	25.91
LL4088F2 (DG)	63.50	8×8	52.70	8.20	22.89	140.0	1440.0/323725	1670.0	42.39

堆高机用板式链

Leaf chains for sky stacker




链板组合
Plate bcing



4×4



6×6



8×8




10×10

东华链号 Donghua Chain No.	节距 Pitch	链板组合 Plate bcing	链板高度 Plate depth	链板厚度 Plate thickness	销轴直径 Pin diameter	销轴长度 Pin length	抗拉强度 Tensile strength	平均抗拉强度 Average tensile strength	每米长重 Weight per meter
	P		h_2 max	T max	d_2 max	L max	Q_{min} kN/bf	Q_0 kN	q kg/m
	mm		mm	mm	mm	mm			
LL3244 (DG)	50.80	4×4	42.00	6.40	17.81	65.0	520.0/116895	598.0	13.73
LL3266 (DG)		6×6				90.8	780.0/175344	897.0	19.94
LL3288 (DG)		8×8				117.0	1040.0/233792	1196.0	26.10
LL321010F10 (DG)	50.80	10×10	42.00	6.00	17.81	134.3	1300.0/292240	1430.0	30.89
LL4066F5 (DG)	63.50	6×6	52.70	8.00	22.89	112.7	1080.0/242794	1245.0	32.59
LL4088F4 (DG)	63.50	8×8	52.70	8.00	22.89	144.0	1400.0/314720	1540.0	42.38


LH系列板式链连接环

Clevises for LH series leaf chains

外连接环
Outside clevis




内连接环
Inside clevis




连接环形式
Clevis type

外连接环
Outside clevis



内连接环
Inside clevis



连接环的尺寸代号
Dimension symbols of clevis


ISO 链号 ISO Chain No.	ANSI 链号 ANSI Chain No.	b7 mm	b8 mm	b9 mm	b10 mm	b11 max mm	b12 min mm	b13 max mm	b14 max mm	p1 nom mm	d1 min mm	h4 min mm	r max mm
LH0822	BL422	-	4.41	-	-	4.03	3.12	-	-	-	5.11	6.35	6.35
LH0823	BL423	-	6.53	-	-	6.05	3.12	-	-	-			
LH0834	BL434	2.21	4.33	10.68	-	4.03	3.12	10.20	-	6.35			
LH0844	BL444	4.41	4.41	12.89	-	4.03	3.12	12.25	-	8.47			
LH0846	BL446	4.41	6.53	17.12	-	6.05	3.12	16.32	-	10.59			
LH0866	BL466	4.41	4.41	12.89	21.36	4.03	3.12	12.25	20.47	8.47	5.98	7.92	7.92
LH1022	BL522	-	5.24	-	-	4.80	3.72	-	-	-			
LH1023	BL523	-	7.76	-	-	7.20	3.72	-	-	-			
LH1034	BL534	2.62	5.14	12.69	-	4.80	3.72	12.12	-	7.55			
LH1044	BL544	5.24	5.24	15.31	-	4.80	3.72	14.56	-	10.07			
LH1046	BL546	5.24	7.76	20.35	-	7.20	3.72	19.40	-	12.59	7.96	9.53	9.53
LH1066	BL566	5.24	5.24	15.31	25.38	4.80	3.72	14.56	24.31	10.07			
LH1222	BL622	-	6.96	-	-	6.41	4.95	-	-	-			
LH1223	BL623	-	10.31	-	-	9.61	4.95	-	-	-			
LH1234	BL634	3.48	6.83	16.88	-	6.41	4.95	16.18	-	10.05			
LH1244	BL644	6.96	6.96	20.36	-	6.41	4.95	19.43	-	13.40	9.56	12.70	12.70
LH1246	BL646	6.96	10.31	27.06	-	9.61	4.95	25.89	-	16.75			
LH1266	BL666	6.96	6.96	20.36	33.76	6.41	4.95	19.43	32.45	13.40			
LH1622	BL822	-	8.59	-	-	7.93	6.13	-	-	-			
LH1623	BL823	-	12.73	-	-	11.89	6.13	-	-	-			
LH1634	BL834	4.29	8.43	20.86	-	7.93	6.13	19.97	-	12.42	9.56	12.70	12.70
LH1644	BL844	8.59	8.59	25.15	-	7.93	6.13	23.98	-	16.56			
LH1646	BL846	8.59	12.73	33.43	-	11.89	6.13	31.96	-	20.70			
LH1666	BL866	8.59	8.59	25.15	41.71	7.93	6.13	23.98	40.04	16.56			

注：1-连接销轴 2-连接链节^a
 Note: 1-connecting pin 2-connecting link^a
^a-连接链节应使用具有过盈配合的外链板
^a-the connecting link should be used with a press fit outer plate


LH系列板式链连接环

Clevises for LH series leaf chains

外连接环
Outside clevis




内连接环
Inside clevis




连接环形式
Clevis type

外连接环
Outside clevis



内连接环
Inside clevis



连接环的尺寸代号
Dimension symbols of clevis

ISO 链号 ISO Chain No.	ANSI 链号 ANSI Chain No.	b7	b8	b9	b10	b11 max	b12 min	b13 max	b14 max	p1 nom	d1 min	h4 min	r max
		mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
LH 2022	BL1022	-	10.26	-	-	9.48	7.35	-	-	-	11.14	15.88	15.88
LH 2023	BL1023	-	15.21	-	-	14.22	7.35	-	-	-			
LH 2034	BL1034	5.13	10.08	24.93	-	9.48	7.35	23.86	-	14.85			
LH 2044	BL1044	10.26	10.26	30.06	-	9.48	7.35	28.65	-	19.80			
LH 2046	BL1046	10.26	15.21	39.96	-	14.22	7.35	38.18	-	24.75			
LH 2066	BL1066	10.26	10.26	30.06	49.86	9.48	7.35	28.65	47.82	19.80	12.74	19.05	19.05
LH 2422	BL1222	-	12.05	-	-	11.16	8.66	-	-	-			
LH 2423	BL1223	-	17.87	-	-	16.74	8.66	-	-	-			
LH 2434	BL1234	6.02	11.84	29.31	-	11.16	8.66	28.05	-	17.46			
LH 2444	BL1244	12.05	12.05	35.33	-	11.16	8.66	33.68	-	23.28			
LH 2446	BL1246	12.05	17.87	46.97	-	16.74	8.66	44.89	-	29.10	14.31	22.23	22.23
LH 2466	BL1266	12.05	12.05	35.33	58.61	11.16	8.66	33.68	56.20	23.28			
LH 2822	BL1422	-	13.76	-	-	12.76	9.90	-	-	-			
LH 2823	BL1423	-	20.41	-	-	19.13	9.90	-	-	-			
LH 2834	BL1434	6.88	13.53	33.48	-	12.76	9.90	32.04	-	19.95			
LH 2844	BL1444	13.76	13.76	40.36	-	12.76	9.90	38.47	-	26.60	17.49	25.40	25.40
LH 2846	BL1446	13.76	20.41	53.66	-	19.13	9.90	51.28	-	33.25			
LH 2866	BL1466	13.76	13.76	40.36	66.97	12.76	9.90	38.47	64.18	26.60			
LH 3222	BL1622	-	15.65	-	-	14.53	11.28	-	-	-			
LH 3223	BL1623	-	23.22	-	-	21.80	11.28	-	-	-			
LH 3234	BL1634	7.82	15.40	38.11	-	14.53	11.28	36.48	-	22.71	23.83	31.75	31.75
LH 3244	BL1644	15.65	15.65	45.93	-	14.53	11.28	43.80	-	30.28			
LH 3246	BL1646	15.65	23.22	61.07	-	21.80	11.28	58.38	-	37.85			
LH 3266	BL1666	15.65	15.65	45.93	76.22	14.53	11.28	43.80	73.07	30.28			
LH 4022	BL2022	-	20.53	-	-	19.19	14.86	-	-	-			
LH 4023	BL2023	-	30.49	-	-	28.78	14.86	-	-	-	23.83	31.75	31.75
LH 4034	BL2034	10.27	20.23	50.11	-	19.19	14.86	48.11	-	29.88			
LH 4044	BL2044	20.53	20.53	60.37	-	19.19	14.86	57.76	-	39.84			
LH 4046	BL2046	20.53	30.49	80.30	-	28.78	14.86	76.99	-	49.80			
LH 4066	BL2066	20.53	20.53	60.37	100.22	19.19	14.86	57.76	96.33	39.84			


注: 1-连接销轴 2-连接链节^a
Note: 1-connecting pin 2-connecting link^a

a-连接链节应使用具有过盈配合的外链板
a- the connecting link should be used with a press fit outer plate


LL系列板式链连接环

Clevises for LL series leaf chains

外连接环
Outside clevis




内连接环
Inside clevis




连接环形式
Clevis type

外连接环
Outside clevis



内连接环
Inside clevis



连接环的尺寸代号
Dimension symbols of clevis


ISO 链号 ISO Chain No.	b7	b8	b9	b10	b11 max	b12 min	b13 max	b14 max	p1 nom	d1 min	h4 min	r max
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
LL0822	-	3.35	-	-	2.97	2.33	-	-	-	-	-	-
LL0844	3.35	3.35	9.71	-	2.97	2.33	9.07	-	6.35	4.46	6.00	6.35
LL0866	3.35	3.35	9.71	16.06	2.97	2.33	9.07	15.17	6.35	-	-	-
LL1022	-	3.58	-	-	3.14	2.48	-	-	-	-	-	-
LL1044	3.58	3.58	10.33	-	3.14	2.48	9.58	-	6.75	5.09	8.00	7.92
LL1066	3.58	3.58	10.33	17.08	3.14	2.48	9.58	16.01	6.75	-	-	-
LL1222	-	4.16	-	-	3.61	2.85	-	-	-	-	-	-
LL1244	4.16	4.16	11.96	-	3.61	2.85	11.03	-	7.80	5.73	9.00	9.52
LL1266	4.16	4.16	11.96	19.76	3.61	2.85	11.03	18.45	7.80	-	-	-
LL1622	-	6.81	-	-	6.15	4.80	-	-	-	-	-	-
LL1644	6.81	6.81	19.81	-	6.15	4.80	18.64	-	13.00	8.30	12.00	12.70
LL1666	6.81	6.81	19.81	32.81	6.15	4.80	18.64	31.14	13.00	-	-	-
LL2022	-	7.86	-	-	7.08	5.55	-	-	-	-	-	-
LL2044	7.86	7.86	22.86	-	7.08	5.55	21.45	-	15.00	10.21	14.00	15.88
LL2066	7.86	7.86	22.86	37.86	7.08	5.55	21.45	35.82	15.00	-	-	-
LL2422	-	10.91	-	-	10.02	7.80	-	-	-	-	-	-
LL2444	10.91	10.91	31.91	-	10.02	7.80	30.26	-	21.00	14.65	18.00	19.05
LL2466	10.91	10.91	31.91	52.91	10.02	7.80	30.26	50.50	21.00	-	-	-
LL2822	-	13.46	-	-	12.46	9.68	-	-	-	-	-	-
LL2844	13.46	13.46	39.46	-	12.46	9.68	37.57	-	26.00	15.92	20.00	22.20
LL2866	13.46	13.46	39.46	65.47	12.46	9.68	37.57	62.68	26.00	-	-	-
LL3222	-	13.51	-	-	12.39	9.68	-	-	-	-	-	-
LL3244	13.51	13.51	39.51	-	12.39	9.68	37.38	-	26.00	17.83	23.00	25.40
LL3266	13.51	13.51	39.51	65.52	12.39	9.68	37.38	62.37	26.00	-	-	-
LL4022	-	17.21	-	-	15.87	12.38	-	-	-	-	-	-
LL4044	17.21	17.21	50.41	-	15.87	12.38	47.80	-	33.20	22.91	28.00	31.75
LL4066	17.21	17.21	50.41	83.62	15.87	12.38	47.80	79.73	33.20	-	-	-
LL4822	-	21.41	-	-	19.84	15.45	-	-	-	-	-	-
LL4844	21.41	21.41	62.82	-	19.84	15.45	59.72	-	41.40	29.26	34.00	38.10
LL4866	21.41	21.41	62.82	104.20	19.84	15.45	59.72	99.60	41.40	-	-	-

注: 1-连接销轴 2-连接链节^a
Note: 1-connecting pin 2-connecting link^a

^a-连接链节应使用具有过盈配合的外链板
^a-the connecting link should be used with a press fit outer plate

LH系列板式链连接销轴 Clevises pin (LH series)


连接销轴
Connecting pin



ISO 链号 ISO Chain No.	ANSI 链号 ANSI Chain No.	孔距 Width between holes	销轴长度 Pin length	销轴直径 Pin diameter	孔径 Hole diameter
		X min	L max	d2 max	D
		mm	mm	mm	mm
LH0822	BL422	10.8	17.2	5.08	1.6
LH0823	BL423	12.9	19.3		
LH0834	BL434	17.0	23.4		
LH0844	BL444	19.2	25.6		
LH0846	BL446	23.5	29.9		
LH0866	BL466	27.7	34.1		
LH1022	BL522	12.8	20.8	5.94	2.0
LH1023	BL523	15.3	23.3		
LH1034	BL534	20.2	28.2		
LH1044	BL544	22.9	30.9		
LH1046	BL546	27.9	35.9		
LH1066	BL566	32.9	40.9		
LH1222	BL622	17.0	29.8	7.92	3.2
LH1223	BL623	20.3	33.1		
LH1234	BL634	26.9	39.7		
LH1244	BL644	30.4	43.2		
LH1246	BL646	37.1	49.9		
LH1266	BL666	43.8	56.6		
LH1622	BL822	21.0	33.8	9.53	3.2
LH1623	BL823	25.1	37.9		
LH1634	BL834	33.2	46.0		
LH1644	BL844	37.5	50.3		
LH1646	BL846	45.8	58.6		
LH1666	BL866	54.1	66.9		
LH2022	BL1022	25.1	41.1	11.10	4.0
LH2023	BL1023	30.0	46.0		
LH2034	BL1034	39.7	55.7		
LH2044	BL1044	44.9	60.9		
LH2046	BL1046	54.8	70.8		
LH2066	BL1066	64.7	80.7		

LH系列板式链连接销轴 Clevises pin (LH series)

连接销轴
Connecting pin




ISO 链号 ISO Chain No.	ANSI 链号 ANSI Chain No.	孔距 Width between holes	销轴长度 Pin length	销轴直径 Pin diameter	孔径 Hole diameter
		X min	L max	d2 max	D
		mm	mm	mm	mm
LH 2422	BL1222	29.5	45.5	12.70	4.0
LH 2423	BL1223	35.3	51.3		
LH 2434	BL1234	46.7	62.7		
LH 2444	BL1244	52.8	68.8		
LH 2446	BL1246	64.4	80.4		
LH 2466	BL1266	76.0	92.0		
LH 2822	BL1422	33.7	49.7	14.27	4.0
LH 2823	BL1423	40.3	56.3		
LH 2834	BL1434	53.4	69.4		
LH 2844	BL1444	60.3	76.3		
LH 2846	BL1446	73.6	89.6		
LH 2866	BL1466	86.9	102.9		
LH 3222	BL1622	38.3	58.3	17.46	5.0
LH 3223	BL1623	45.9	65.9		
LH 3234	BL1634	60.8	80.8		
LH 3244	BL1644	68.6	88.6		
LH 3246	BL1646	83.7	103.7		
LH 3266	BL1666	98.9	118.9		
LH 4022	BL2022	50.4	70.4	23.81	5.0
LH 4023	BL2023	60.3	80.3		
LH 4034	BL2034	79.9	99.9		
LH 4044	BL2044	90.2	110.2		
LH 4046	BL2046	110.1	130.1		
LH 4066	BL2066	130.0	150.0		

LL系列板式链连接销轴

Clevises pin (LL series)


连接销轴
Connecting pin



ISO 链号 ISO Chain No.	孔距 Width between holes	销轴长度 Pin length	销轴直径 Pin diameter	孔径 Hole diameter
	X min	L max	d2 max	D
	mm	mm	mm	mm
LL0822	8.1	14.5	4.45	1.6
LL0844	14.5	20.9		
LL0866	20.8	27.2		
LL1022	8.6	15.0	5.08	1.6
LL1044	15.4	21.8		
LL1066	22.1	28.5		
LL1222	10.0	18.0	5.72	2.0
LL1244	17.8	25.8		
LL1266	25.6	33.6		
LL1622	16.5	29.3	8.28	3.2
LL1644	29.5	42.3		
LL1666	42.5	55.3		
LL2022	19.1	31.9	10.19	3.2
LL2044	34.1	46.9		
LL2066	49.1	61.9		
LL2422	26.6	42.6	14.63	4.0
LL2444	47.6	63.6		
LL2466	68.6	84.6		
LL2822	32.9	48.9	15.90	4.0
LL2844	58.9	74.9		
LL2866	84.9	100.9		
LL3222	33.0	53.0	17.81	5.0
LL3244	59.0	79.0		
LL3266	85.0	105.0		
LL4022	42.1	67.3	22.89	6.3
LL4044	75.3	100.5		
LL4066	108.5	133.7		
LL4822	52.4	77.6	29.24	6.3
LL4844	93.8	119.0		
LL4866	135.2	160.4		

LL系列板式链连接销轴 Clevises pin (LL series)


连接销轴
Connecting pin




东华链号 Donghua Chain No.	孔距 Width between holes	销轴长度 Pin length	销轴直径 Pin diameter	孔径 Hole diameter
	X _{min}	L _{max}	d2 _{max}	D
	mm	mm	mm	mm
LL2466 (DG)	67.7	85.0	14.63	5.0
LL2844 (DGF1)	66.0	83.4	15.90	5.0
LL2866 (DG)	73.6	90.8		5.0
LL3266 (DGF1)	85.7	104.0	17.81	5.0
LL3288 (DGF2)	117.0	134.0		5.0
LL3244F2 (DG)	73.2	90.2		4.7
LL3266F6 (DG)	85.7	104.0		5.0
LL4066 (DG)	104.3	125.3	22.89	6.3
LL4088F2 (DG)	169.0	195.0		6.0

多板销轴链

Gall's chains




链板组合
Plate lacing



东华链号 Donghua Chain No.	节距 Pitch	内节内宽 Width between inner plates	链板组合 Plate lacing	销轴直径 Pin diameter		销轴长度 Pin length	链板高度 Plate depth	链板厚度 Plate thickness	抗拉强度 Tensile strength	每米长重 Weight per meter
	P	b ₁ mm		d ₁ max	d ₂ max	L max	h ₂ max	T max	Q min	q
	mm	mm		mm	mm	mm	mm	mm	kN/bf	kg/m
MP15	15	12	2×2	5	4	25	12	2.03	5.0/1125	0.7
MP20	20	15	2×2	8	6	28	15	2.03	12.5/2812	1.1
MP25	25	18	2×2	10	8	36	18	3.00	25.0/5624	1.8
MP30	30	20	4×4	11	9	51	20	3.00	40.0/8999	3.4
MP35	35	22	4×4	12	10	53	26	3.00	60.0/13498	4.5
MP40	40	25	4×4	14	12	58	32	3.00	80.0/17998	5.0
MP45	45	30	4×4	17	14	63	35	3.00	100.0/22497	7.0
MP50	50	35	4×4	22	18	90	40	4.50	150.0/33746	11.3
MP55	55	40	4×4	24	21	108	42	6.00	200.0/44994	14.5
MP60	60	45	4×4	26	23	114	46	6.00	250.0/56243	17.1
MP70	70	50	6×6	32	28	148	55	6.00	375.0/84364	34.0
MP80	80	60	6×6	36	32	159	60	6.00	500.0/112486	39.0
MP90	90	70	6×6	40	36	184	70	7.00	750.0/168728	53.0
MP100	100	80	8×8	45	40	224	80	7.00	1000.0/224972	77.0
MP110	110	90	8×8	50	45	236	90	7.00	1250.0/281215	90.0
MP120	120	100	8×8	55	50	262	100	8.00	1500.0/337458	112.0

多板销轴链 Gall's chains


链板组合
Plate bcing



东华链号 Donghua Chan No.	节距 Pitch	内节内宽 Width between innerplates	链板组合 Plate bcing	销轴直径 Pin diameter		销轴长度 Pin length	链板高度 Plate depth	链板厚度 Plate thickness	抗拉强度 Tensile strength	每米长重 Weight per meter
	P	b1 min		d1 max	d2 max	L max	h2 max	T max	Q min	q
	mm	mm		mm	mm	mm	mm	mm	kN/bf	kg/m
LF30	30.0	16.5	2×2	6.0	5.00	27.7	15.7	2.03	20.0/4496	0.72
M P50F2	50.0	38.0	6×6	22.0	18.00	85.0	40.0	3.00	250.0/56202	11.11
M P50.8	50.8	36.0	6×6	22.0	17.81	85.4	42.0	3.25	200.0/44961	11.90
M P70F1	70.0	21.0	2×2	16.5	14.00	51.5	30.5	6.00	145.0/32597	4.16
M P70F2	70.0	50.0	8×8	32.0	28.00	158.0	55.0	5.00	375.0/84303	44.00
M P70F3	70.0	52.0	8×8	32.0	28.00	160.0	55.0	5.00	375.0/84303	31.62
M P80F1	80.0	60.0	8×8	36.0	32.00	170.0	60.0	5.00	500.0/112404	35.32
*M P90F2	90.0	60.4	6×6	40.0	37.00	182.0	70.0	8.00	700.0/157366	52.70
*M P90F1	90.0	60.0	4×4	36.0	32.00	146.0	60.0	8.00	600.0/134885	32.22
*M P110F1	110.0	90.0	8×8	50.0	45.00	239.0	90.0	7.00	1250.0/281011	87.50


注：*表示链板为直边形，销轴两端带垫圈
Note: *means straight link plate, both end of pin with washer

停车库链条 Car parking chains



东华链号 Donghua Chain No.	节距 Pitch	滚子直径 Roller diameter	内节内宽 Width between inner plates	销轴直径 Pin diameter	销轴长度 Pin length		内链板高度 Inner plate depth	链板厚度 Plate thickness	螺栓规格 Bolt type	抗拉强度 Tensile strength	平均抗拉强度 Average tensile strength	每米长重 Weight per meter
	P	d1 max	b1 min	d2 max	L max	Lc max	h2 max	T max	M	Q min	Q0	q
	mm	mm	mm	mm	mm	mm	mm	mm	mm	kN/bf	kN	kg/m
16ALT-1	25.40	15.88	15.75	7.92	32.7	36.5	24.0	3.25	M 20	71.55/16261	81.8	2.60
16ALT-2	25.40	15.88	15.75	7.92	62.7	65.8	24.0	3.25	M 20	143.10/32523	166.3	5.15
20ALT-1	31.75	19.05	18.90	9.53	40.4	44.7	30.0	4.00	M 24	107.85/24511	118.6	3.91
20ALT-2	31.75	19.05	18.90	9.53	76.4	80.5	30.0	4.00	M 24	215.70/49023	234.4	7.80
20ALT-3	31.75	19.05	18.90	9.53	112.2	116.3	30.0	4.00	M 24	323.55/73534	351.6	11.77
24ALT-1	38.10	22.23	25.22	11.10	50.3	54.3	35.7	4.80	M 30	149.20/330909	161.1	5.62
24ALT-2	38.10	22.23	25.22	11.10	95.8	99.7	35.7	4.80	M 30	298.40/67818	322.2	11.70


停车库链条 Car parking chains



东华链号 Donghua Chain No.	节距 Pitch	套筒直径 Boush diameter	滚子直径 Roller diameter		内节内宽 Width between inner plates	销轴直径 Pin diameter	销轴长度 Pin length	链板高度 Plate depth	链板厚度 Plate thickness	附件尺寸 Attachment dimension				抗拉强度 Tensile strength
	P	d1 max	d4 min	d5 min	b1	d2 max	L max	h2	t/T	C	H	L1	L2	Q min
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kN/bf
P450F1	450.0	85.0	137.0	158.0	75	55	153	171	16/14	630	160	178	278	1800/404640
P450F2	450.0	85.0	136.5	180.0	75	55	174	171	16/14	675	170	166	282	1764/396547
P450F4	450.0	85.0	136.5	180.0	75	55	174	171	16/14	630	160	166	282	1764/396547

停车库链条

Car parking chains




东华链号 Donghua Chain No.	节距 Pitch	滚子直径 Roller diameter			内节内宽 Width between inner plates	销轴直径 Pin diameter			销轴长度 Pin length			链板高度 Plate depth	链板厚度 Plate thickness		附件尺寸 Attachment dimension			抗拉强度 Tensile strength
	p	d1 max	d5 min	b1	d2 max	L max	Lc max	L1 max	h2	t/T	C	d4	H1	Q min				kN/bf
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	
P 450F5	450	120	138	56	30	120	130	174	80	12.0/30.0	672	160	19	450.0/101160				
P 450F6	450	120	140	84	36	150	159	210	100	12.0/30.0	672	160	19	800.0/179840				
P 450F13	450	120	140	84	36	150	159	210	100	12.0/30.0	675	135	13	800.0/179840				
*P 460F1	460	118	138	51	36	-	134.5	173.5	90	14.0/20.0	665	110.4	-	650.0/146120				
P 460F2	460	120	140	84	36	150	159	202	100	12.0/25.0	675	135	13	800.0/179840				
P 460F3	460	130	144	60	36	126	135	185	100	12.0/30.0	650	110	-	800.0/179840				
P 460F5	460	100	119	55	30	118	130	160	75	12.0/20.0	570	107	-	650.0/146120				

*滚轮内带轴承

*With bearing inside roller

无滚子提升链 Rollerless hoisting chains



东华链号 Donghua Chain No.	节距 Pitch	套筒直径 Bush diameter	内节内宽 Width between inner plates	销轴直径 Pin diameter	销轴长度 Pin length		内链板高度 Inner plate depth	链板厚度 Plate thickness	抗拉强度 Tensile strength	平均抗拉强度 Average tensile strength	每米长重 Weight per meter
	P	d_1 max	b_1 min	d_2 max	L max	Lc max	h_2 max	T max	Q min	Q ₀	q
	mm	mm	mm	mm	mm	mm	mm	mm	kN/bf	kN	kg/m
45-1	12.700	5.63	7.85	3.96	16.6	17.8	12.00	1.50	14.10/3205	17.5	0.54
55-1	15.875	7.03	9.40	5.08	20.7	22.2	15.09	2.03	22.20/5045	29.4	0.83
65-1	19.050	8.33	12.57	5.94	25.9	27.7	18.00	2.42	31.80/7227	41.5	1.22
85-1	25.400	11.10	15.75	7.92	32.7	35.0	24.00	3.25	56.70/12886	69.4	2.16
105-1	31.750	13.60	18.90	9.53	40.4	44.7	30.00	4.00	88.50/20114	109.2	3.31
125-1	38.100	15.60	25.22	11.10	50.3	54.3	35.70	4.80	127.00/28864	156.3	4.97
145-1	44.450	18.00	25.22	12.70	54.4	59.0	41.00	5.60	172.40/39182	212.0	6.50
165-1	50.800	20.00	31.55	14.27	64.8	69.6	47.80	6.40	226.80/51545	278.9	8.70